



# EZ9110 Heavy-duty Filtration System, pore size 50 μm

Termékszám: EZ9110.XX310031

HUF Ár (nettó): Elérhetőségünk

Elérhető

## Universal self-cleaning filtration for difficult samples - compatible with all EZ Series online analysers

#### About the EZ9100 Series

The successful implementation of online analysers in process control strategies could not have been achieved without the development of a new generation of automatic sampling and sample preconditioning systems. The EZ9100 Series are the result of many years of field experience in combining analysers with filtration units.

#### Simplified operation by self-cleaning action

All preconditioning systems are designed for fully automatic operation and require virtually no human intervention. A blowback action by instrument air is incorporated in all systems. This fundamental design principle does not merely allow trouble-free sampling, moreover it contributes to high uptimes.

The EZ9110 is a filtration system developed to make solid-free samples from heavily charged liquids available for online analysis. Devoid of overly complex engineering, they can handle the difficult properties of wastewaters charged with high levels of insoluble constituents:

- Self-cleaning sample filtration with various pore sizes
- Large-bore pneumatic ball valves for sample and drain
- Automatic cleaning by solenoid controlled instrument air
- Static Pressure Regulator assures a constant, readily available sample level at atmospheric pressure
- PLC or analyser controlled cleaning frequency

### Műszaki adatok

Anyag: Filter: SS 316L

Piping: PVC

Manual ball valves:PVC

Tubing: Norprene, PFA, PE

Panel: weather resistant Trespa

Cleaning: Automatic blowback by solenoid controlled instrument air

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm<sup>2</sup>

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Különleges jegyzet: Backflush valve controlled by Analyzer

Lefolyócső: Overflow sample D=50 mm; overflow Static Pressure Regulator 3/8" OD

Méretek (MxSZxM): 1150 mm x 750 mm x 200 mm

Minta hőmérséklet: Max. 65 °C Mintautak száma: 1 stream

Optional:

1 to 8 streams

Required fast loop: 2 m/s Size:  $50 \mu \text{m}$ 

Speciális tulajdonság: Heavy Duty (Std)

Súly: 18 kg Szemcseméret: 50 µm

Optional:

 $100~\mu m,\,200~\mu m$ 

Teljesítmény: 24 VDC, powered by analyser

Védettségi osztály: IP55