



EZ7900 Toxicity Analyser

Termékszám: EZ7900.XXXXXXXXXX
HUF Ár (nettó): Elérhetőségünk

Online, automatic respirometry for early warning of toxicity in wastewater treatment plants

Early Warning System against calamities

The EZ7900 Online Toxicity Analyser is able to detect and measure waste water streams that present an acute or chronic toxicity to the biomass of a water treatment plant. This allows operators to take corrective measures to protect the viability of the activated sludge.

Representative measurements on fresh sludge

Measurements are carried out on real sludge freshly sampled from the treatment plant by means of a self-cleaning sampling-filtration system (option). This unique approach has the following advantages: dynamic changes in biomass viability are immediately detected, while sample temperature and pH in the analysis vessel reflects those of the treatment plant.

The EZ7900 Series combine a unique, field-proven respirometric analyser design with a robust sampling-filtration system, assuring detection of toxic compounds or shock loads in an early stage:

- Detection of acute and chronic toxicity on activated sludge
- Measurement of the respiration rate by means of a single dissolved oxygen (DO) sensor
- Smart automatic features
- Standard 4 - 20 mA signal output with alarm processing
- Communication ports supporting connectivity to Modbus
- Multiple stream analysis

There are many additional options available. Please contact Hach for more details.

Műszaki adatok

A doboz tartalma:	EZ7900 Toxicity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings
Analóg kimenetek:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Anyag:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated

Automatikus tisztítás:	Igen
Demineralised water:	N.A.
Detektálási határ:	N.A.
Digitális kimenetek:	Optional: Modbus (TCP/IP, RS485)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ²
Garancia:	24 hónap
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferenciák:	N.A.
Kalibrálás:	Automatic; standard at every analysis cycle
Környezeti hőmérséklet:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Lefolyócső:	Atmospheric pressure, vented, min. Ø 32 mm
Mérés módszer:	Respirometry
Méréstartomány:	0 - 100 % inhibition
Méreték (MxSZxM):	690 mm x 465 mm x 330 mm
Minta hőmérséklet:	10 - 30 °C
Minta minőség:	Maximum particle size 500 µm, < 0.1 g/L
	Most applications require the use of a dual EZ9110 + EZ9120 sampling/filtration system.
Minta: nyomás:	By external overflow vessel
Mintaáram:	100 - 300 mL/min
Mintacellák:	10 - 15 minutes
Mintautak száma:	1, 2, or 4
Paraméter:	Toxicity; respiration rate
Pontosság:	Better than 5% full scale range for standard test solutions
Reagent Requirements:	Keep between 10 - 30 °C
Riasztás:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Súly:	25 kg
Tanúsítványok:	CE compliant / ETL certified
Teljesítmény:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Validation:	Automatic; frequency freely programmable
Védettségi osztály:	Analyser cabinet: IP44 / Panel PC: IP65

A doboz tartalma

EZ7900 Toxicity Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings